

**Optional Items**



**Laser Cutter**

Specification	
Model Name	<b>X500III Pro</b>
Laser Source	100W      130W      150W
Laser Cooling	Sealed CO <sub>2</sub> Laser
Laser Cooling	Water Cooled
Working Area	w/o Honeycomb Table      51 x 36 in. (1300 x 916 mm)
	with Honeycomb Table      50.3 x 35.2 in. (1280 x 896 mm)
Max. Part Size (L x W x H)	w/o Cutting Table      52.9 x 36.0 x 2.1 in. (1346 x 916 x 55 mm)
	Doors Open      52.9 x ∞ x 1.1 in. ( 1346 x ∞ x 30 mm )
	With Honeycomb Cutting Table      48.8 x 32.2 x 1.1 in. (1240 x 818 x 30 mm)
	With Aluminum Cutting Table      52.1 x 35 x 1.1 in. (1325 x 889 x 30 mm)
Dimensions	74.8 x 55.1 x 47.2 in. (1900 x 1400 x 1200 mm)
Driver	Closed-loop DC Servo Control
Maximum Cutting Speed*	40 IPS
Speed Control	Adjustable from 0.1~100% ( Up to 16 color-linked speed settings per job )
Power Control	Adjustable from 0~100% ( Up to 16 color-linked speed settings per job )
Engraving Capability	256-level gray scale image processing capability
Distance Accuracy	0.254 mm or 0.1% of move, whichever is greater
Z-Axis Movement	Manual
Resolution (DPI)	Available 125, 250, 300, 500, 600, 1000
Interface	10 Base-T Ethernet USB Type-A 2.0  – For USB storage (Max. 32GB capacity, FAT file system) USB Type-B 2.0  – For connecting with the computer
Focus Lens	Standard 2", Optional 3"      Standard 3", Optional 2"
Display Panel	4-line LCD panel showing current file name, total working time, laser power, engraving speed, file(s) loaded into memory buffer, setup and diagnostic menus.
Safety	Class I Laser Product Compliant with EN60825, Class II Laser Product Compliant with CDRH, 2006/42/EC Machinery Directive Compliance, Class 4 Laser Product Compliant with CDRH with the optional pass-through door module
Cutting Table	Knife-shaped cutting bars with down vacuum and scrap collecting funnel
Operation Voltage	200-240VAC, 50/60Hz auto switching, Max.10A
Air Exhaust System	External exhaust system with minimum flow rate 2160m <sup>3</sup> /h (CFM 1273 ft <sup>3</sup> /min) is required, 2.5kPa negative pressure (Pure-Air PA-2400FS @ 8" exhaust port)

\* Speed does not equal to throughput. See dealer or visit [www.GCCworld.com](http://www.GCCworld.com) for more details.

Δ Specifications are subject to change without prior notice.

\*\*\* Please use certified brands by GCC for LaserPro USB storage, kindly refer to GCC User Manuals for more details.

Authorized Dealer





[www.GCCworld.com](http://www.GCCworld.com)



# GCC LaserPro X500III Pro

Professional Cutting Performance at The Best Value




## X500III Pro

- Spacious 51.1 x 36.1 mm working area
- 1.6X beam expander for uniformity of line width and spot size
- DC Servo Motor Technology for precise movement control
- Uniquely innovative user-friendly features
- Fullfill versatile cutting and engraving applications



GCC Headquarters	4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan	886-2-6616-6692	Fax : 886-2-2694-6875
GCC China	No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China	86-512-5726-1515	Fax : 86-512-5726-1518
GCC Europe B.V.	Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands	31-10-458-9367	
GCC America, Inc	20453 E Valley Blvd. Walnut, CA 91789, USA	1-909-718-0248	Fax : 1-909-718-0251
		US & Canada Only	Toll Free: 1-888-284-5211



Laser Cutter

# GCC LaserPro X500III Pro




## GCC LaserPro X500III Pro

Embrace the cutting technology from the GCC LaserPro X500III designed and engineered for professional use. Moreover, GCC releases X500III Pro version for advanced cutting quality and uniformity of line width by adding one beam expander and red beam combiner.

Packed with several user-friendly features, the GCC LaserPro X500III Pro offers high product performance in terms of both durability and feasibility. The X500III Pro model combines cutting and engraving capabilities to give users a versatile system.


### Beam Expander

X500III Pro includes one 1.6X beam expander for uniformity of line width that presents outstanding quality and reliability.



### New Design of X500III Pro Carriage

Advanced X500III Pro carriage design to increase the stability of the carriage movement, elevate the performance of X500III Pro.




### Knife-shaped Cutting Table

Unique cutting table with tipped bars that can be easily adjusted without tools to create different levels of working depths. The cutting table of X500III Pro reduces laser reflections and delivers clear cutting edge.



### Intuitive Control Panel Interface

A control panel with coherent hot-key design and graphic icon displays that allows you to directly change the laser parameter setting, set jobs to repeat unlimited times, queue job, delete jobs, and more.



### Closed-loop DC Servo Technology

The X500III Pro utilizes high performance closed-loop DC servo motors for precise and fast carriage movement combined with a reliable motion system to produce exceptionally accurate outputs.



### Key Switch & Emergency Stop

Key switch safeguards the machine from unauthorized use. Prominent emergency button located on the top of the machine allows operators to stop the laser and the motion carriage immediately to provide a safe operating environment.



### Drag-N-Play

The "Drag-N-Play" feature greatly reduces complex set up procedures and allows users to directly drag the lens carriage to the starting point of a job.



### Versatile Cutting & Engraving Capability

X500III Pro delivers high cutting quality with LaserPro's unique laser firing control technology. X500III Pro can cut through 20 mm acrylic in a single pass. Better than that, the grayscale technology allows X500III Pro to process 256-level grayscale image with vivid engraving quality.